



# eneo MPC-52A0010M0B

SKU: 241967



1/3" HD Camera, 1920x1080, 10x AF Zoom  
5,1-51mm, T-WDR, HD-SDI, EX-SDI, TVI, Composite

## Main Features

- 
- 1/2,8" 2,0 Megapixel Sony CMOS-Sensor
- 
- Resolution max. 1920x1080, 1080p@60/50fps
- 
- Optical 10x Auto Focus Zoom, 5,1~51mm
- 
- Multisignal Output HD-SDI, EX-SDI, TVI, Composite
- 
- WDR 120dB, DNR, motion detector
- 
- Digital noise reduction (2D+3D)
- 

- 
- Image stabilization, privacy masking, defog
- 
- Privacy Masking, Defog
- 
- Slow Speed Shutter
- 
- Compact Housing
- 
- Power Supply 12VDC
- 

## Specifications

General	
Lighting	No
Dimensions (WxHxD) (extended)	62,2x59,2x99,6mm
Weight	0.36 kg
Text overlay	available
Color (Housing)	silvermetallic,black
Housing type	Inside
Housing material	Aluminium
Power consumption	3 W
Power supply	12VDC

# eneo MPC-52A0010M0B

Continuation of the specifications

Temperature Range (Operating)	-10°C ~ +50°C,@ Luftfeuchtigkeit 90% oder weniger (nicht kondensierend)
Wide Dynamic Range (WDR)	WDR 120dB
<b>Camera</b>	
Backlight compensation	Yes
Low Speed Shutter	Yes
Recording sensor	CMOS
Chip size	1/2,8"
Flickerless function	Yes
Camera shape	Zoom cameras
Signal-to-noise ratio	50 dB
Day/night mode	Automatic,Day,Night,extern (Sensor)
White balance	AUTO
Photosensitivity	0,003 Lux
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
<b>Display</b>	
Image resolution max.	1920x1080
<b>DORI</b>	
Watch (62px/m)	31,3 - 302,4 m
Detect (125px/m)	15,2 - 150,3 m
Identify (250px/m)	7,5 - 75,5 m
Perceiving (25px/m)	78 - 763 m
<b>Functions</b>	
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Analysis	Motion Detection
Menu languages	Chinese, English, Japanese
<b>Interfaces / Inputs/ Outputs</b>	
Number of alarm outputs	1
External connections	1x SDI Signal (BNC), 1x HD/SD Analog Signal (BNC), 12VDC power input, RS-485, external day&night switching, Alarm output
Interface Protocols	Pelco D, Pelco P
Control Interfaces	Coaxitron (HD Protocol), RS-485
Video Outputs	Composite (FBAS)
<b>Parts supplied</b>	
Scope of delivery	manual
<b>Lens</b>	
Horizontal angle of view	57 - 6,2°
Vertical angle of view	34 - 3,5°
Focal length	5,1 - 51 mm

# eneo MPC-52A0010M0B

Continuation of the specifications

Aperture Range (F)	F1.6~F1.8
Lens Type	Auto Focus Zoom
Zoom Factor (Digital)	0
Zoomfactor (optical)	10
<b>Video</b>	
Resolution (extended)	1920x1080,1280x720
Signal Format	Composite (FBAS), EX-SDI @ 2MP, HD-SDI @ 2MP, HD-TVI @ 2MP
Horizontal resolution	700 TVL
<b>Product labeling:</b>	
Manufacturer order number	241967

## Optional Accessory

SKU	Name	Description
219504	eneo WD-30	Wall Mount Bracket with Ball Joint, 1/4" Camera Fixing Screw, Pantone Cool Grey 1C

## Optional Services

SKU	Name	Description
214441	PAINTING SERVICE basic costs	once per RAL color and delivery lot
211123	PAINTING SERVICE bullet camera	in RAL color
229233	Vorkonfiguration analoge Kamera	Preconfiguration 1x analog camera Function test, FW update

## Your contact person

VIDEOR E. Hartig GmbH  
 Carl-Zeiss-Straße 8  
 63322 Rödermark  
 Germany

