eneo NSUI-3008M0A

SKU: 242370
EAN: 4260229841624



Gigabit Switch Industrial, Unmanaged, 8x PoE, 2xSFP, 30W each Port, -40°C~75°C, 44~57 VDC, w/o power supply

Main Features

- 8 RJ45 ports with 10/100/1000 Mbps
- 2 Gigabit SFP port for fiber optic uplink
- 8 PoE+ ports, each with up to 30W power
- Total PoE power: up to 222 watts,
- depending on the connection
- Supports IEEE 802.3af/at standards
- High EMC protection level
- Plug-and-play, no configuration, easy to use.
- Redundant power supply 44-57VDC
- Robust IP30 housing, DIN-RAIL or wall mounting
- Operating temperature range: -40-75°C
- Power supply not included

Specifications

General	
Fan	No
Number of PoE ports	8
Design	DIN Rail Module
Dimensions (WxHxD) (extended)	50x149,2x122mm
ESD protection	IEC61000-4-2, IEC61000-4-5
Weight	1.168 kg
Type	Unmanaged
Power consumption	18 W
Mounting type	DIN Rail, Wall

© Copyright VIDEOR E. Hartig GmbH - October 2026 - technical changes reserved

eneo NSUI-3008M0A

Continuation of the specifications

PoE Budget (Total)	222 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Power supply	44-57VDC
Temperature Range (Operating)	-40°C ~ +75°C,@ Luftfeuchtigkeit 10%-90% (nicht kondensierend)
Notes	
Remark	No power supply included. A suitable,optionally available power supply must be used to achieve the full specified PoE budget value.
Interfaces / Inputs/ Outputs	
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Parts supplied	
Scope of delivery	manual,1x DIN Rail
Network	
Eneo _netzwerkstandards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3x Flow Control
Internal Switching Capacity (Gbit)	20 Gbps
Internal Switching Capacity (MP per second)	14.88 Mpps
Product labeling:	
EAN/GTIN	4260229841624
Manufacturer order number	242370
Series	eneo Switch

Optional Accessory

SKU	Name	Description
244698	eneo NSFP-00100RJ45	SFP module, transceiver, RJ45 connection, Cat.6A, supports 10G/5G/2.5 G/1G Ethernet up to 50m range, CAT6a, hot-pluggable
245203	eneo NSFP-00300DLC-Multimode	SFP module, transceiver, Multi Mode, 1250Mbps, up to 550m distance, Duplex LC optical connector
242377	eneo NSFP-20000DLC	SFP Module, 1.25 Gbps, 20KM, Duplex LC, Tx/Rx at 1310 nm, hot-plug, SFP MSA-compliant, Digital Monitoring
242376	eneo NSFP-20000SLC	SFP Modul Pair, 1.25 Gbps, 20 km, Simplex LC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring
242375	eneo NSFP-20000SSC	SFP Modul Pair, 1,25Gbps, 20KM, Simplex SC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring
242374	eneo NSFP-3000SLC	SFP Modul Pair, 1,25Gbps, 3KM, Simplex LC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring

© Copyright VIDEOR E. Hartig GmbH - October 2026 - technical changes reserved

eneo NSUI-3008M0A

242373	eneo NSFP-3000SSC	SFP Modul Pair, 1,25Gbps, 3KM, Simplex SC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring

© Copyright VIDEOR E. Hartig GmbH - October 2026 - technical changes reserved

eneo NSUI-3008M0A

Continuation of accessory

218759	eneo SFP-0850M10-10G	SFP Modul, 10Gbps, 300m, Multimode, 850nm, Duplex LC Connector, -5°~+70°C
218758	eneo SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216567	eneo SFP-0850MM10	SFP Modul, 155Mbps , 2km, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
216478	eneo SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
218760	eneo SFP-1310S10-10G	SFP Modul, 10Gbps, 10km, Singlemode, 1310nm, Duplex LC Connector, -5°~+70°C

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

© Copyright VIDEOR E. Hartig GmbH - October 2026 - technical changes reserved