NSFP-3000SSC

SKU: 242373

SFP Modul Pair, 1,25Gbps, 3KM, Simplex SC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring

Main Features

- 1250 Mbps data rate via single-mode fiber
- BIDI design for single-fiber use (1310/1550 nm)
- Up to 3 km range on 9/125 µm SMF
- SC optical connector
- Compliant with SFP MSA & SFF-8472
- Digital Diagnostics (DDM/DOM) integrated
- Single +3.3V power supply required
- Metal housing reduces EMI interference
- Temp. range -40°C to +85°C (industrial)
- TX fault and LOS detection supported
- Low power consumption (max. 300 mA)
- RoHS compliant and lead-free assembly

Specifications

Dimensions (HxWxD)	13,8x13,75x65,2mm
Type	SFP-Modul
Fiber optic connector	Simplex SC
Transmission medium	optical fiber
Model	module
Number of fibers	2
Wavelength	1310nm
Range	3 km
Operating temperature	0°C ~ +70°C
Weight	43g

© Copyright VIDEOR E. Hartig GmbH - June 2025 - technical changes reserved

NSFP-3000SSC

Continuation of the specifications

Manufacturer order number	242373

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

© Copyright VIDEOR E. Hartig GmbH - June 2025 - technical changes reserved