eneo NSFP-20000SLC

SKU: 242376
EAN: 4260229841686



SFP Modul Pair, 1.25 Gbps, 20 km, Simplex LC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring

Main Features

- 1250 Mbps data rate via single-mode fiber
- BIDI design for single-fiber use (1310/1550nm)
- Up to 20 km range on 9/125 µm SMF
- LC optical connector
- Compliant with SFP MSA & SFF-8472
- Digital Diagnostics (DDM/DOM) integrated
- Single +3.3V power supply required
- Metal housing reduces EMI interference
- Wide temp. range: -40°C to +85°C (industrial)
- TX fault and LOS detection supported
- Low power consumption (max. 300 mA)
- RoHS compliant and lead-free assembly

Specifications

General	
Number of fibers	1
Design	Module
Dimensions (WxHxD) (extended)	14,5x12,5x56,3mm
Application environment	inside
Weight	37.47 kg
Transmission medium	Glass fibre
Type	SFP Module
Reach	20 km
Temperature Range (Operating)	-40°C ~ +85°C

© Copyright VIDEOR E. Hartig GmbH - October 2026 - technical changes reserved

eneo NSFP-20000SLC

Continuation of the specifications

Wavelength	1310nm, 1550nm
Recording	
Mode	Single Mode
Interfaces / Inputs/ Outputs	
Fiber Optic Connectors	Duplex LC
Product labeling:	
EAN/GTIN	4260229841686
Manufacturer order number	242376

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

© Copyright VIDEOR E. Hartig GmbH - October 2026 - technical changes reserved