eneo NSFP-20000DLC

SKU: 242377
EAN: 4260229841693



SFP Module, 1.25 Gbps, 20KM, Duplex LC, Tx/Rx at 1310 nm, hot-plug, SFP MSA-compliant, Digital Monitoring

Main Features

- 1250 Mbps data rate on 9/125 µm SMF
- Dual-fiber design (separate TX and RX fibers)
- Up to 20 km range (single-mode fiber)
- LC optical connector
- Compliant with SFP MSA & SFF-8472
- Integrated Digital Diagnostics Monitoring (DDM)
- Wide temp. range: -40°C to +85°C (industrial)
- Single 3.3V power supply
- Metal housing for low EMI interference
- TX fault and Loss of Signal (LOS) alerts
- Low power consumption (< 300 mA)
- RoHS compliant and lead-free

Specifications

General	
Number of fibers	2
Design	Module
Dimensions (WxHxD) (extended)	14,2x12,5x56,3mm
Application environment	inside
Weight	0.17 kg
Transmission medium	Glass fibre
Type	SFP Module
Reach	20 km
Temperature Range (Operating)	-40°C ~ +85°C

© Copyright VIDEOR E. Hartig GmbH - October 2026 - technical changes reserved

eneo NSFP-20000DLC

Continuation of the specifications

Wavelength	1310nm
Recording	
Mode	Single Mode
Interfaces / Inputs/ Outputs	
Fiber Optic Connectors	Duplex LC
Product labeling:	
EAN/GTIN	4260229841693
Manufacturer order number	242377

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

© Copyright VIDEOR E. Hartig GmbH - October 2026 - technical changes reserved