ISM-42F0037MMB

SKU: 243236

1/2,8" Mini Network Modul Camera, 1920x1080, Day&Night, 3DNR, 3,7mm, Pinhole, 12VDC, PoE, Indoor

Main Features

- 1/2.8" Sony STARVIS CMOS image sensor
- Resolution max. 1920x1080 (Full HD)
- Video Compression Format: H.264/MJPEG
- Motion Detection, Low Speed Shutter
- Built in SD micro card slot
- Backlight compensation 3DNR and D-WDR
- Supports privacy zones and corridor mode
- Lens 3.6mm (further lenses upon request)
- Power Supply 12VDC (1.8W) or PoE (IEEE802.3af)
- Connection cable (RJ45) for PoE and power supply
- Operation Temperature -20°C - +50°C
- Supports ONVIF Profile S

Specifications

Dimensions (HxWxD)	36x36x14mm
Series	eneo ISM-Serie
Resolution Standard	HD 1080p
System	electronic Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	30 fps
Day&Night switch	Electronic

© Copyright VIDEOR E. Hartig GmbH - June 2025 - technical changes reserved

ISM-42F0037MMB

Continuation of the specifications

Low Speed Shutter	yes
Digital Noise Reduction	yes
Backlight Compensation	BLC
Wide Dynamic Range (WDR)	D-WDR
Motion Detector	yes
Focal Length	3,7 mm
Iris Control	no
Horizontal Angle of View	69,38°
Vertical Angle of View	36,87°
MOD (Mininum Object Distance)	0,3 m
Housing	Indoor
Color (housing)	black
Hosuing material	Metal
Heater	no
Blower	no
Alarm inputs	nein
Alarm outputs	no
Audio support	no
Ethernet interface	100Base-TX, 10Base-T
Internal storage	microSD-Kartenslot
Analysis functions	Motion detection
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, PoE
Power consumption	1,4W at 12VDC, 2,5W at PoE
Power over Ethernet	IEEE 802.3af
Vandal proof	no
Operating temperature	-20°C ~ +50°C
ONVIF	ONVIF Profile S
Camera type	Modul, Platine
Remote configuration	Browser
Weight	45g
Manufacturer order number	243236

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products

Optional Services

SKU	Name	Description

© Copyright VIDEOR E. Hartig GmbH - June 2025 - technical changes reserved

ISM-42F0037MMB

Continuation of services

229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

© Copyright VIDEOR E. Hartig GmbH - June 2025 - technical changes reserved