



eneo MPD-62M2713P0B

SKU: 243652



HD Analogue Dome Fixed, WDR, Day&Night, 2.7-13,5mm, Infrare 1920x1080, 12VDC, Indoor

Main Features

1/2.8" 2 Megapixel SONY STARVIS 2 CMOS sensor	Removable infrared cut filter
Resolution max. 1920x1080 pixels (Full HD)	ROI (Region of Interest) WDR mode
Super low light performance by Sony STARVIS 2 technology	Integrated motion detector, defog, privacy zones
Multisignal: HD-TVI, AHD, CVI and Composite selectable	Wedge adapter included (10° inclination)
Digital signal: EX-SDI, HD-SDI selectable	Scratch resistant hard coated bubble
Motorized vari-focal lens 2.7~13.5mm	Easy installation, 3-Axis gimbal

Specifications

General	
Lighting	Infrared
Dimensions (WxHxD) (extended)	94x116mm
Illumination range	ca. 30m
Weight	0.26 kg
Text overlay	available
Color (Housing)	white
Housing type	Inside
Housing material	Plastic
Power consumption	6 W

eneo MPD-62M2713P0B

Continuation of the specifications

Mounting type	Ceiling, Wall
Power supply	12VDC
Temperature Range (Operating)	-10°C ~ +50°C
Wide Dynamic Range (WDR)	D-WDR
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Recording sensor	CMOS
Chip size	1/2,8"
Flickerless function	Yes
Camera shape	Minsters
Signal-to-noise ratio	50 dB
Day/night mode	Automatic,Day,Night,extern (Sensor)
White balance	Automatic,Preset,Manual,AUTOext
Photosensitivity	0.005Lux(Day mode),0.0005Lux(Night mode)
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	1920x1080
DORI	
Watch (62px/m)	18 - 52 m
Detect (125px/m)	8 - 25 m
Identify (250px/m)	4 - 12 m
Perceiving (25px/m)	47 - 128 m
Functions	
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Menu languages	Chinese, English, French, German, Japanese, Korean
Notes	
Remark	NDAA compliance under Section 889
Interfaces / Inputs/ Outputs	
External connections	voltage input, 1x SDI Signal (BNC), 1x HD/SD Analog Signal (BNC),connection cable approx. 15cm
Interface Protocols	UTC (HD Signal Format)
Control Interfaces	Coaxitron (HD Protocol)
Video Outputs	AHD, Composite (FBAS)
Parts supplied	
Scope of delivery	manual,drilling template,bag of screws
Lens	
Horizontal angle of view	101 - 32°

eneo MPD-62M2713P0B

Continuation of the specifications

Vertical angle of view	54 - 18°
Focal length	2,7 - 13,5 mm
Aperture Range (F)	F1.6
Lens Type	Varifocal (motorized)
Zoom Factor (Digital)	0
Zoomfactor (optical)	4
Video	
Resolution (extended)	1920x1080,1280x720,720x576
Signal Format	AHD @ 2MP, Composite (FBAS), HD-TVI @ 2MP
Product labeling:	
Manufacturer order number	243652
Series	eneo KX-Serie,eneo Callisto Indoor

Optional Services

SKU	Name	Description
214441	PAINTING SERVICE basic costs	once per RAL color and delivery lot
211125	PAINTING SERVICE fix dome camera	in RAL color
229233	Vorkonfiguration analoge Kamera	Preconfiguration 1x analog camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
 Carl-Zeiss-Straße 8
 63322 Rödermark
 Germany

