




eneo MSM-42F0037MPB

SKU: 243654



1/2.8" HD Board Camera, Colour, 1920x1080, 3.7mm, Pinhole, WDR, Housing, 12VDC

Main Features

1/2,8" 2 Megapixel SONY STARVIS 2 CMOS-Sensor	Digital signal: EX-SDI, HD-SDI selectable
Super low light performance by Sony STARVIS 2 technology	Pinhole lens 3.7mm
Board Camera with rugged metal cabinet	Electronic Day/Night function
Resolution max. 1920x1080 (Full HD)	ROI (Region of Interest) WDR mode
Separate outputs for digital and multi-signal	Integrated motion detector, defog, privacy zones
Multisignal: HD-TVI, AHD, CVI and Composite selectable	

Specifications

General	
Dimensions (WxHxD) (extended)	37x37,8x21,5mm
Weight	0.11 kg
Text overlay	available
Color (Housing)	black
Housing type	Inside
Housing material	Aluminium
Camera Type	Board Camera
Power consumption	1.5 W
Mounting type	Ceiling, Wall

eneo MSM-42F0037MPB

Continuation of the specifications

Power supply	12VDC
Temperature Range (Operating)	-10°C ~ +50°C,@ Luftfeuchtigkeit 20%-80% (nicht kondensierend)
Wide Dynamic Range (WDR)	D-WDR
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Recording sensor	CMOS
Chip size	1/2,8"
Camera shape	Module
Signal-to-noise ratio	50 dB
Day/night mode	Automatic,Day,Night,extern (Sensor)
White balance	Automatic,Preset,Manual,AUTOext
Photosensitivity	0,2 Lux bei F2,3
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	1920x1080
DORI	
Watch (62px/m)	21 m
Detect (125px/m)	11 m
Identify (250px/m)	5 m
Perceiving (25px/m)	59 m
Functions	
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Menu languages	Chinese, English, French, German, Japanese, Korean
Notes	
Remark	NDAA compliance under Section 889
Interfaces / Inputs/ Outputs	
Alarm inputs	0
Number of alarm outputs	0
External connections	voltage input, 1x SDI Signal (BNC), 1x HD/SD Analog Signal (BNC)
Interface Protocols	UTC (HD Signal Format)
Control Interfaces	Coaxitron (HD Protocol)
Video Outputs	AHD, Composite (FBAS)
Parts supplied	
Scope of delivery	manual,mounting accessories
Lens	
Horizontal angle of view	72°

eneo MSM-42F0037MPB

Continuation of the specifications

Vertical angle of view	37°
Iris Control	No
Focal length	3,7 mm
Lens Type	Prime lens
Zoom Factor (Digital)	0
Video	
Resolution (extended)	1920x1080, 1280x720, 704x576, 720x480
Signal Format	AHD @ 2MP, Composite (FBAS), EX-SDI @ 2MP, HD-SDI @ 2MP, HD-TVI @ 2MP
Product labeling:	
Manufacturer order number	243654
Series	eneo COAXIZE

Optional Services

SKU	Name	Description
229233	Vorkonfiguration analoge Kamera	Preconfiguration 1x analog camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
 Carl-Zeiss-Straße 8
 63322 Rödermark
 Germany

