eneo MPC-52C0000M0B

SKU: 243655
EAN: 4260229841334



1/2.8" HD Camera, Day&Night, 1920x1080, WDR, C/CS, 12VDC

Main Features

1/2.8" 2 Megapixel SONY STARVIS 2 CMOS sensor	Digital signal: EX-SDI, HD-SDI selectable
Super low light performance by Sony STARVIS 2 technology	Removable infrared cut filter
Resolution max. 1920x1080 pixels (Full HD)	ROI (Region of Interest) WDR mode
Separate outputs for digital and multi-signal	Integrated motion detector, defog, privacy zones
Multisignal: HD-TVI, AHD, CVI and Composite selectable	C/CS mount, LSC (Lens shading compensation)

Specifications

General	
Dimensions (WxHxD) (extended)	72x74x89mm
Weight	0.29 kg
Text overlay	available
Color (Housing)	Pantone Cool Gray 1C
Housing type	Inside
Housing material	Aluminium
Power consumption	3.5 W
Power supply	12VDC
Temperature Range (Operating)	-10°C ~ +50°C,@ Luftfeuchtigkeit 20%-80% (nicht kondensierend)

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo MPC-52C0000M0B

Continuation of the specifications

Wide Dynamic Range (WDR)	D-WDR
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Recording sensor	CMOS
Chip size	1/2,8"
Flickerless function	Yes
Camera shape	Box
Signal-to-noise ratio	50 dB
Day/night mode	Automatic,Day,Night,extern (Sensor)
White balance	Automatic,Preset,Manual,AUTOext
Photosensitivity	0.005Lux @F1,6 (Day mode),0.0005Lux(Night mode)
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	1920x1080
Functions	
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Menu languages	Chinese, English, French, German, Japanese, Korean
Notes	
Remark	NDAA compliance under Section 889
Interfaces / Inputs/ Outputs	
Alarm inputs	0
Number of alarm outputs	0
External connections	voltage input,1x SDI Signal (BNC),1x HD/SD Analog Signal (BNC)
Interface Protocols	UTC (HD Signal Format)
Control Interfaces	Coaxitron (HD Protocol)
Video Outputs	AHD, Composite (FBAS)
Parts supplied	
Scope of delivery	Quick installation guide,dust cap,Allen wrench,C/CS adapter
Video	
Resolution (extended)	1920x1080,1280x720,720x576,720x480
Signal Format	AHD @ 2MP, Composite (FBAS), EX-SDI @ 2MP, HD-SDI @ 2MP, HD-TVI @ 2MP
Product labeling:	
EAN/GTIN	4260229841334
Manufacturer order number	243655
Series	eneo COAXIZE

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo MPC-52C0000M0B

Continuation of the specifications

Optional Accessory

SKU	Name	Description
213619	eneo H04Z03NFDC-MP	F1,5/4-13mm, Megapixel DC-Lens, variable Focal Lenght, 1/1.8" CS-Mount

Optional Services

SKU	Name	Description
214441	PAINTING SERVICE basic costs	once per RAL color and delivery lot
211123	PAINTING SERVICE bullet camera	in RAL color
229233	Vorkonfiguration analoge Kamera	Preconfiguration 1x analog camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

VIDEOR

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved