



eneo IND-45F0022M0B

SKU: 246620
EAN: 4260229840900



Mini Network Dome Camera Fix, 2880x1620,
Day/Night, WDR, AI 2,2mm, IR, 12VDC, PoE, IP66

Main Features

1/2.7" CMOS sensor, maximum resolution 5 MP/30fps	Supports ONVIF profiles S/T/G/M
AI analysis functions including object classification	Multilingual menu navigation (OSD)
WDR 120dB, 3D-DNR noise reduction	Local storage via Micro SD card
Fixed focal length lens 2.2mm (HFoV 156°)	Supports audio (built-in microphone)
Smart Codec H.265/H.264, multi-streaming	NDA compliance
Browser independent (IE, Edge, Safari, Firefox, Chrome)	IR LED illumination, IP66

Specifications

Other	
EAN/GTIN	4260229840900
Analysis	Crowds (CD), Enter Region, Face, Heat Map (HM), Intrusion, Leave Region, License plate recognition (LPR), Line crossing (LCD), Object classification, Object Classification Human / Vehicle (PD&VD), Passage count (CC), Queues (QD), Rare Sounds (RSD)
Audio support	Yes
Motion detector	Yes

eneo IND-45F0022M0B

Continuation of the specifications

Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Backlight compensation	Yes
Low Speed Shutter	Yes
Audio compression	G.711
Resolution standard	5 MP
Recording sensor	Chipset SSC30KQ, CMOS, SC533HAI
Lighting	Infrared
Image resolution max.	2880x1620
Image transfer rate max.	30 fps
Horizontal angle of view	156°
Vertical angle of view	81°
Focal length	2,2 mm
Chip size	1/2,7"
Dimensions (WxHxD) (extended)	64,3x115,3mm
Alarm processing	Recording internal storage (SD card),E-Mail,HTTP,FTP,TCP,UDP,Cloud Upload
Audio	1 Way Audio, Built-in microphone
Resolution (extended)	2880x1620 (16:9),2592x1520 (16:9),2304x1296 (16:9),1920x1080 (16:9),1280x720 (16:9),640x480 (4:3),320x240 (4:3)
Illumination range	Approx. 20m
Remark	Face and license plate recognition require an SD card or an eneo IN recorder. For optimal results,use only eneo components. For mixed brands,we offer a compatibility check for a fee (info: item #229235 at VIDEOR)
Watch (62px/m)	5,1m
Aperture Range (F)	F2.0
Browser	Edge, Firefox, Google Chrome, MS Internet Explorer 10/11, Safari
Data stream types	Triple-Stream(Main/Sub/Mobile)
Detect (125px/m)	2,3m
ESC	1/5 ~ 1/20.000sec.
External connections	RJ-45,micro SD card slot 256 GB
Flickerless function	Yes
Weight	0.3 kg
Identify (250px/m)	1,3m
Camera shape	Minsters
Scope of delivery	Quick installation guide,drilling template,3x wall plugs with screws,1x Torx wrench,1x rubber gasket,1x snagless RJ45 boot
Manual Electric Shutter (MES)	1-5~1-20,000sec.

eneo IND-45F0022M0B

Continuation of the specifications

Menu languages	English, French, German, Italian, Japanese, Portuguese, Spanish, Turkish
Password	Administrator and User
Privacy Zone	Areas-ON/OFF switchable
SDK	Upon request
Security	Complicated password, IP address filtering
Signal-to-noise ratio	43 dB
Day/night mode	Automatic,Day,Night,Image,Time
Text overlay	Switchable on/off
Perceiving (25px/m)	14,6m
White balance	Automatic,Manual
Ethernet interface	100Base-TX, 10Base-T
Color (Housing)	RAL9003,Other colors available upon request
Color (dome)	clear
Housing type	Outside
Housing material	Aluminium, Plastic
Internal memory	microSD card slot
Camera Type	Domecamera
Power consumption	5 W
Photosensitivity	0.004lux bei F1.6(AGC ON)
MOD (Minimum Object Distance)	0.2 m
Mounting type	Ceiling, Wall
Network Protocols	DDNS, DHCP, DNA, FTP, HTTP, HTTPS, NTP, RTP, RTSP, SMTP, TCP-IP, UPnP
Lens Type	Prime lens
ONVIF	ONVIF Profile G, ONVIF Profile M, ONVIF Profile S, ONVIF Profile T
Manufacturer order number	246620
Power over Ethernet	IEEE 802.3af
Protection	IP66, NEMA 4X
Series	eneo IN-Serie
Control Interfaces	Ethernet
Power supply	Poe
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Temperature Range (Operating)	-35°C ~ +60°C,@ Luftfeuchtigkeit 90% oder weniger (nicht kondensierend)
Video Compression	H.264, H.264+, H.265, H.265+, MJPEG
Wide Dynamic Range (WDR)	WDR 120dB

Optional Accessory

SKU	Name	Description
-----	------	-------------

eneo IND-45F0022M0B

Continuation of accessory

234989	eneo INsight	Control software for recorder IN- and MN-series
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
234990	eneo INsight mobile	Mobile App for recorder IN- and MN-series
218218	eneo Site Manager	Management Software for eneo IP products

Optional Services

SKU	Name	Description
214441	PAINTING SERVICE basic costs	once per RAL color and delivery lot
211125	PAINTING SERVICE fix dome camera	in RAL color
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

