eneo IND-42M2808M0A

SKU: 246625
EAN: 4260229841846



Mini Network Dome Camera Fix, 1920x1080, Day/Night, WDR, AI 2,8-8mm, IR, 12VDC, PoE, IP66, IK10

Main Features

1/2.8" Sony STARVIS CMOS sensor,2 MP/60fps	Supports ONVIF profiles S/T/G/M
AI analysis functions including object classification	Multilingual menu navigation (OSD)
WDR 120dB, 3D-DNR Noise Reduction	Local storage via Micro SD card
Motorized varifocal lens 2.8-8mm	Supports audio and external alarm input and output
Smart Codec H.265/H.264, multi-streaming	NDAA compliance
Browser independent (IE, Edge, Safari, Firefox, Chrome)	IR LED illumination, IP66 and vandal proof IK10

Specifications

Other	
EAN/GTIN	4260229841846
Analysis	Crowds (CD), Enter Region, Face Recognition (FR), Heat Map (HM), Intrusion, Leave Region, License plate recognition (LPR), Line crossing (LCD), Object Classification Human / Vehicle (PD&VD), Passage count (CC), Queues (QD), Rare Sounds (RSD)
Audio support	Yes
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo IND-42M2808M0A

Continuation of the specifications

Multicast	Yes
Backlight compensation	Yes
Low Speed Shutter	Yes
Vandalism-resistant	Yes
Alarm inputs	1
Audio compression	G.711
Resolution standard	2 MP
Recording sensor	CMOS, SC235HAI, SSC30KQ
Lighting	Infrared
Image resolution max.	1920x1080
Image transfer rate max.	60 fps
Horizontal angle of view	100° - 44°
Vertical angle of view	56° - 25°
Focal length	2,8 - 8 mm
Chip size	1/2,9"
Turning range	350 °
Dimensions (WxHxD) (extended)	115x91,6mm
Alarm processing	Recording internal storage (SD card),E-Mail,HTTP,FTP,TCP,UDP,alarm out,Cloud Upload
Audio	2 Way Audio
Resolution (extended)	1920x1080 (16:9),1280x960 (4:3),1280x720 (16:9),640x480 (4:3),320x240 (4:3)
Illumination range	Approx. 20m
Remark	Face and license plate recognition require an SD card or an eneo IN recorder. For optimal results,use only eneo components. For mixed brands,we offer a compatibility check for a fee (info: item #229235 at VIDEOR).
Watch (63px/m)	13,9 - 38,7m
Picture size	16:9, 4:3
Aperture Range (F)	F1.8
Browser	Edge, Firefox, Google Chrome, MS Internet Explorer 10/11, Safari
Data stream types	Triple-Stream(Main/Sub/Mobile)
Detect (125px/m)	5,5 - 18,7m
ESC	1/5 ~ 1/20.000sec.
External connections	RJ-45,Alarm in/output,Audio input/output,12VDC input (DC plug),connection cable approx.45cm,micro SD card slot 512 GB
Flickerless function	Yes
Weight	0.56 kg
Identify (250px/m)	2,7 - 8,6m
Camera shape	Minsters

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo IND-42M2808M0A

Continuation of the specifications

Scope of delivery	Quick installation guide,drilling template,4 wall plugs with screws,1 Torx wrench,waterproof cover for RJ45 connector
Manual Electric Shutter (MES)	1-5~1-20,000sec.
Menu languages	English, French, German, Italian, Japanese, Portuguese, Spanish, Turkish
Password	Administrator and User
Privacy Zone	Areas-ON/OFF switchable
SDK/API	Upon request
Security	Complicated password, IEEE 802.1X-Authentication (available from firmware version 8.2.4.1), IP address filtering, Password
Signal-to-noise ratio	41 dB
Day/night mode	Automatic,Day,Night,Image,Time
Text overlay	Switchable on/off
Vertical tilt range	0~ +80°
Perceiving (25px/m)	37,3 - 96,9m
White balance	Automatic,Manual
Ethernet interface	100Base-TX, 10Base-T
Color (Housing)	RAL9003,Other colors available upon request
Color (dome)	clear
Housing type	Outside
Housing material	Aluminium
Internal memory	microSD card slot
Camera Type	Domecamera
Power consumption	6.2 W
Photosensitivity	Color 0,0034lux bei F1.6(AGC ON)
MOD (Minimum Object Distance)	0.8 m
Mounting type	Ceiling, Wall
Network Protocols	DDNS, DHCP, DNA, FTP, HTTP, HTTPS, NTP, RTP, RTSP, SMTP, TCP-IP, UPnP
Lens Type	Varifocal (motorized)
ONVIF	ONVIF Profile G, ONVIF Profile M, ONVIF Profile S, ONVIF Profile T
Manufacturer order number	246625
Power over Ethernet	IEEE 802.3af
Protection	IP67
Series	eneo IN-Serie
Control Interfaces	Ethernet
Power supply	12VDC, Poe
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Temperature Range (Operating)	-35°C ~ +60°C,@ Luftfeuchtigkeit 90% oder weniger (nicht kondensierend)

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved

eneo IND-42M2808M0A

Continuation of the specifications

Video Compression	H.264, H.264+, H.265, H.265+, MJPEG
Wide Dynamic Range (WDR)	120dB
Certifications	IK10
Zoomfactor (optical)	3

Optional Accessory

SKU	Name	Description
234753	eneo AK-22	Camera junction box for wall and ceiling mount, Mini Dome IND-42M2808M0A
234754	eneo AK-23	Camera connection box for Mini Dome IND-42M2808M0A for holder Dome-WB6/Dome-CH6
234757	eneo DOME-WB7	Wall bracket for Mini Dome IND-42M2808M0A
234989	eneo INsight	Control software for recorder IN- and MN-series
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
234990	eneo INsight mobile	Mobile App for recorder IN- and MN-series
218218	eneo Site Manager	Management Software for eneo IP products

Optional Services

SKU	Name	Description
214441	PAINTING SERVICE basic costs	once per RAL color and delivery lot
211125	PAINTING SERVICE fix dome camera	in RAL color
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

VIDEOR

© Copyright VIDEOR E. Hartig GmbH - November 2026 - technical changes reserved