



eneo IND-58F0002MTPB

SKU: 246665
EAN: 4260229841884



Network Dome Camera Fix, Turret, Panorama 180°, 2x 5120x1440, Day/Night, DWDR, AI, 2x 2,8mm, IR, White Light, 12VDC, PoE, IP67

Main Features

Multisensor 2x 1/2.7' CMOS sensor, panorama	Smart Codec H.265/H.264, dual streaming
Maximum resolution 5120x1440 pixels each, 15fps	Browser-independent (Edge, Safari, Firefox, Chrome)
Panorama ultra wide-angle camera 180° HFoV, 32:9	Supports ONVIF profiles S/T/G/M and audio
AI analysis functions including object classification	Local storage via micro SD card
WDR, BLC, HLC and 3D-DNR noise reduction	NDA compliance
Lenses with 2.8mm fixed focal length	Integrated IR and white light LED illumination, IP67

Specifications

Other	
EAN/GTIN	4260229841884
Analysis	Crowds (CD), Enter Region, Face, Heat Map (HM), Intrusion, Leave Region, License plate recognition (LPR), Line crossing (LCD), Object classification, Object Classification Human / Vehicle (PD&VD), People counting, Queues (QD), Rare Sounds (RSD)
Audio support	Yes
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes

eneo IND-58F0002MTPB

Continuation of the specifications

Multicast	Yes
Backlight compensation	Yes
Low Speed Shutter	Yes
Audio compression	G.711a, G.711u
Resolution standard	8 MP
Recording sensor	Chipset NT98529, CMOS, SC533HAI
Lighting	Infrared, Warm Light
Image resolution max.	5120x1440
Image transfer rate max.	15 fps
Horizontal angle of view	180°
Vertical angle of view	60°
Focal length	2,8 mm
Chip size	1/2,7"
Dimensions (WxHxD) (extended)	112,4x135 mm
Alarm processing	Recording internal storage (SD card),E-Mail,HTTP,FTP,TCP,UDP,Red & blue flashing lights,Cloud Upload
Audio	2 Way Audio, Built-in microphone, Built-in speaker
Resolution (extended)	5120x1440,4608x1296,4096x1152,3840x1080,3072x864,1536x432,1024x288
Illumination range	Approx. 30 m Approx. 15 m Warm light
Remark	Face and license plate recognition require an SD card or an eneo IN recorder. For optimal results,use only eneo components. For mixed brands,we offer a compatibility check for a fee (info: item #229235 at VIDEOR).
Watch (62px/m)	23,8m
Aperture Range (F)	F1,2
Browser	Edge, Firefox, Google Chrome, MS Internet Explorer 10/11, Safari
Data stream types	Dual Streaming
Detect (125px/m)	11,7m
ESC	1/5 ~ 1/20.000sec.
External connections	RJ-45,12VDC input (DC plug),connection cable approx.30cm,micro SD card slot 256 GB
Flickerless function	Yes
Weight	0.765 kg
Identify (250px/m)	5,5m
Camera shape	Minsters
Scope of delivery	Quick installation guide,drilling template,3x wall plugs with screws,1x Allen wrench,1x waterproof cover for RJ45 connector
Manual Electric Shutter (MES)	1-5~1-20,000sec.
Menu languages	English, French, German, Italian, Japanese, Portuguese, Spanish, Turkish

eneo IND-58F0002MTPB

Continuation of the specifications

Password	Administrator and User
Privacy Zone	Areas-ON/OFF switchable
SDK	Upon request
Security	Complicated password, HTTPS encryption, IP address filtering, Password
Signal-to-noise ratio	49 dB
Day/night mode	Day,Night,Automatic,Time
Text overlay	Switchable on/off
Perceiving (25px/m)	60,1m
White balance	Automatic,Manual
Ethernet interface	100Base-TX, 10Base-T
Color (Housing)	RAL9003,Other colors available upon request
Housing type	Outside
Housing material	Aluminium
Internal memory	microSD card slot
Camera Type	Panoramic camera
Power consumption	13.5 W
Photosensitivity	0.001 Lux bei (F1.6,AGC ON)
MOD (Minimum Object Distance)	2 m
Mounting type	Ceiling, Wall
Network Protocols	DDNS, DHCP, DNS, FTP, HTTP, HTTPS, IPv4, IPv6, NTP, PPPoE, RTP, RTSP, SMTP, TCP-IP, UPnP, UTP
Lens Type	Prime lens
ONVIF	ONVIF Profile G, ONVIF Profile M, ONVIF Profile S, ONVIF Profile T
Manufacturer order number	246665
Power over Ethernet	IEEE 802.3af
Protection	IP67, NEMA 4X
Series	eneo IN-Serie
Control Interfaces	Ethernet
Power supply	12VDC, Poe
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Temperature Range (Operating)	-30°C ~ +60°C,@ Luftfeuchtigkeit 90% oder weniger (nicht kondensierend)
Video Compression	H.264, H.264+, H.265, H.265+, MJPEG
Wide Dynamic Range (WDR)	WDR 120dB

Optional Accessory

SKU	Name	Description
-----	------	-------------

eneo IND-58F0002MTPB

Continuation of accessory

233754	eneo AK-20	Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras
233775	eneo AK-21	Camera connection box for Wall and ceiling mounting, Bullet and Dome Cameras IN series
235339	eneo AK-24	Dual camera connection box for selected Bullet or Fix Dome IN-Series cameras
236663	eneo DOME-WB8	Wall bracket for PTZ dome INP-54M2812M0A and IND-5 Dome Series
234989	eneo INsight	Control software for recorder IN- and MN-series
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
234990	eneo INsight mobile	Mobile App for recorder IN- and MN-series
218218	eneo Site Manager	Management Software for eneo IP products

Optional Services

SKU	Name	Description
214441	PAINTING SERVICE basic costs	once per RAL color and delivery lot
211125	PAINTING SERVICE fix dome camera	in RAL color
229234	Vorkonfiguration IP-Kamera	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Germany

