SFP-1310S10

Article number: 216566

SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C

- Compatible to IEEE802.3z Gigabit Ethernet Standard
- Bandwith 1,25Gbps
- Compliant with Fibre Channel 100-SM-LC-L
- Industry standard small form pluggable (SFP) package
- Duplex LC connector, 1310nm
- Differential LVPECL inputs and outputs
- Single power supply 3.3V
- Hot Pluggable
- Class 1 laser product complies with EN 60825-1
- Distance 9/125 µm SMF 20km

Specifications

Interfaces / Inputs / Outputs:	
Operation mode	single mode
Fiber optic connector	Duplex LC

General:	
Range	20 km
Weight	17g
Temperature range (operation)	0°C ~ +70°C
Wavelength	1310nm

Notes:	
Application	indoor
Number of fibers	2
Transmission medium	optical fiber

© Copyright eneo by VIDEOR E. Hartig GmbH, 12 January 2021 -Technical changes reserved

eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

© Copyright eneo by VIDEOR E. Hartig GmbH, 12 January 2021 -Technical changes reserved