



SOL-IQswitch-4PU-C

Article number: 219802

Camera junction box
with 4-port switch unmanaged
4xPoE, 2xRJ45, 2xSFP 1000Mbps

Ready-to-use junction box solution
incl. SOL-IQbox-budget
incl. Switch IAM-5SE1004MUC
incl. Power supply DR-120-48
Electrically prewired and tested
Optimised for outdoor use
UV stable polycarbonate, corrosion-resistant
Protective class IP66
Impact resistance IK 10, vandalism protected
Swivelling door (with door contact switch)
Wall or mast mounted
Fast, easy installation

SOL-IQswitch-4PU-C is a ready-to-use solution for connecting network cameras. The integrated switch can be used to supply up to 4 IP cameras via PoE. They are connected to a network via Gigabit ports with a network cable or with fibreglass (optional SEP module required).

This solution package consists of the following components:

Junction boxes SOLVIDO SOL-IQbox-budget, eneo Switch IAM-5SE1004MUC, eneo power supply DR-120-48

Specifications

Junction box	Model SOL-IQbox-budget
Housing	UV resistant polycarbonate, RAL 7035, seal: PUR
Door	Swivelling, opening angle 120°
Closure	2-point closure, double bit
Dimensions (LxWxH)	400x300x150mm
Power supply	230VAC
Protective class	IP66, IK10
Switch	Model IAM-5SE1004MUC
Device type	Layer2 Switch
Ethernet interfaces	10Base-T, 100Base-TX, 1000Base-T
VLAN	yes
Ports	4x 10/100/1000Base-T, 2x 10/100/1000T SFP, 2x 10/100/1000Base-TX
Number of PoE ports	4
Management	No
Power over Ethernet	IEEE 802.3at
PoE Budget (total)	120W
Miscellaneous	Surge protection IEC61000-4-5 (6KV)
Power supply	Model DR-120-48
Input voltage range	85-264VAC
Output voltage	48VDC
Power	120W