eneo MPC-52A0010M0A

Articlenumber: 233051

Short description

1/3" HD Camera, 1920x1080, 10x AF Zoom 5,1-51mm, T-WDR, HD-SDI, EX-SDI, TVI, Composite

Key features

- 1/3" 2,0 Megapixel Panasonic CMOS-Sensor
- Resolution max. 1920x1080, 1080p@60/50fps
- Optical 10x Auto Focus Zoom, 5,1~51mm
- Multisignal Output HD-SDI, EX-SDI, TVI, Composite
- Real time True WDR
- Digital Noise Reduction(2D+3D)
- Digital Image Stabilization
- Privacy Masking, Defog
- Slow Speed Shutter
- Compact Housing
- Power Supply 12VDC

© Copyright VIDEOR E. Hartig GmbH - November 2026 - Subject to technical changes

Features

Product Labels	
Manufacturer number	233051
Camera	
Camera shape	Zoom cameras
Chip size	1/3"
Photosensitivity	0,5 Lux bei F1,6, 50 IRE
Recording sensor	CMOS
System	True Day&Night
Low Speed Shutter	Yes
Flickerless function	Yes
Backlight compensation	Yes
Day/night switching	Switchable IR Filter (ICR)
Day/night mode	Automatic, Day, Night, extern (Sensor)
White balance	AUTO, One push, Manual, Indoor, Outdoor
Signal-to-noise ratio	50 dB
Video	
Signal Format	HD-TVI @ 2MP, EX-SDI @ 2MP, HD-SDI @ 2MP, Composite (FBAS)
Horizontal resolution	700 TVL
Lens	
Lens Type	Auto Focus Zoom
Focal length	5,1 - 51 mm
Zoom Factor (Digital)	0
Aperture Range (F)	F1.6~F1.8
Vertical angle of view	31 - 4,0°
Horizontal angle of view	54 - 4,9°
Iris Control	DC
Zoomfactor (optical)	10
Display / Presentation	
Image resolution max.	1920x1080, 1280x720
DORI	
Perceiving (25px/m)	78 - 763 m
Watch (62px/m)	31,3 - 302,4 m

© Copyright VIDEOR E. Hartig GmbH - November 2026 - Subject to technical changes

Continuation Features

Detect (125px/m)	15,2 - 150,3 m
Identify (250px/m)	7,5 - 75,5 m
Features	
Motion detector	Yes
Analysis	Motion Detection
Menu languages	English, Japanese, Chinese
Digital Noise Reduction (DNR)	Yes
Interfaces / Inputs / Outputs	
Video Outputs	HD-TVI, HD-SDI, Composite (FBAS)
External connections	1x SDI Signal (BNC), 1x HD/SD Analog Signal (BNC), 12VDC power input, RS-485, external day&night switching, Alarm output
Number of alarm outputs	1
Control Interfaces	RS-485, Coaxitron (HD Protocol)
Interface Protocols	Pelco P, Pelco D, UTC (HD Signal Format)
General	
Wide Dynamic Range (WDR)	WDR 120dB
Lighting	No
Dimensions (WxHxD) (extended)	62x59x100mm
Weight	0.42 kg
Color (Housing)	silvermetallic, black
Housing type	Inside
Housing material	Aluminium
Power consumption	3 W
Power supply	12VDC
Temperature Range (Operating)	-10°C ~ +50°C
Text overlay	available
Scope of Delivery	
Scope of delivery	manual

© Copyright VIDEOR E. Hartig GmbH - November 2026 - Subject to technical changes

eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

© Copyright VIDEOR E. Hartig GmbH - November 2026 - Subject to technical changes