



IQbox-budget C

Article number: 246003

camera junction box for
video security applications,
400x300x210mm

Optimised for outdoor use
Electrically prewired for flexible, modular expansion.
UV stable polycarbonate, corrosion-resistant
Protective class IP66
Impact resistance IK 10,
Vandalism protected
Including electrical circuit breaker
Swivelling door (with door contact switch)
Fast, easy installation
Wall or mast mounted
Simple mechanical finishing

Junction box for universal expansion with a wide variety of components from different manufacturers and designs. The additional components can be mounted on the TS35 mounting rails without tools.

Specifications

Housing:	UV resistant polycarbonate, RAL 7035, Sealing: PUR
Door:	Swivel-mounted, opening angle 120°
External dimensions:	400x300x210mm
Protection class:	IP66, IK10
Temperature range:	-40°C ~ +80°C
Cable entries:	1x M20 for mains input up to max. 3x2.5mm ² 4x M25 with a split inner sealing ring (IP66) for RJ45 plug 4x M20 1x M16 All cable entries factory-fitted with sealing plugs
Voltage input:	230V/50Hz
Mounting plate:	2x TS35/7.5 mounting rails, bottom one raised by 20 mm Mains input terminals up to max. 3x2.5 mm ²
Mounting plate included:	1 x Siemens 5SY4106-6 single-pole circuit breaker B6 (6A) 2x 2-conductor terminals for tamper contact
Safety:	2x control cabinet lock, 2-point double-bit
Weight:	6,5 Kg
Other:	2x pressure compensation element mounted

Your Contact



Solvido is a registered trademark of

VIDEOR E. Hartig GmbH

Carl-Zeiss-Straße 8

63322 Rödermark

Deutschland

Telefon: +49 6074-888-111

E-Mail: info@videor.com

Internet: www.videor.com