



EDC-OPS-2/24V

Article number: 74136

Pendant Mount Outdoor Dome Housing with Sunshield, Tinted Bubble 6.5", 24VAC

Outdoor housing for Fastrax I - III dome cameras

Tinted bubble 6.5" (165mm)

Prepared for wall and ceiling mounting

Sunshield, heater and blower kit included

Supply voltage: 24VAC/50-60Hz

Protection rating: IP66

Option: Wall and ceiling mount brackets, power box

Option: Connection cable #74143 & #74144

Specifications

Colour (housing)	Pantone Cool Gray 1C
Colour (bubble)	tinted
Housing	outdoor
Housing material	aluminium
Weight	3,6kg
Heater	yes
Camera fixing	dome
Bubble	165mm (6.5"), tinted acrylic plastic
Power consumption	approx. 75W for heater, blower and incl. dome camera
Mounting	wall or ceiling pendant mount
Protection rating	IP66
Supply voltage	24VAC, 50/60Hz
Temperature range (operation)	-45°C ~ +50°C
Load capacity	approx. 2kg
Categorie	Housings

Product recommendations



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

